



INDUSTRIES LIMITED

29 Keeling Road, Henderson,
P.O. Box 21-233,
Auckland, New Zealand.
Telephone: (09) 836-4685.

JENNY ASSEMBLY INSTRUCTIONS

Congratulations on selecting a Jenny spinning wheel. We know it will give you many hours of pleasure.

Your spinning wheel is crafted from Tawa, a New Zealand native timber that has been kiln dried. If you have a natural finished wheel, before spinning we recommend you seal the timber by using a linseed or teakwood oil, polyurethane or similar.

The grain in the timber may be enhanced by using a stain. An oil-based stain is generally slow-drying and non-grain raising, making it easier to obtain a uniform colour. Seek the advice of your paint stockist if you are not familiar with the application and compatibility of the stain and finishing product, as each has its own characteristics.

Maintenance

This is IMPORTANT. To maintain your Jenny spinning wheel in efficient working order, we recommend using a medium grade oil:

- When a bobbin is changed: 1 drop of oil to the maiden bearings
2 drops to the flyer shaft
- Weekly: 2 drops of oil to the footman/crank bearing
- Monthly: 1 drop of oil to the two wheel bearings and two treadle bar pins.

If you have one of our polished wheels, use a premium grade furniture polish to clean and maintain the high quality finish.

Manufacturers of

